



Technical Data Sheet

Finishing profile for dimpled membranes GXP

Technical Data:

Length:	2,0 lm
Height:	68 mm
Colour:	graphite, black
Raw material:	hard PVC
Unit package:	film wrapping, quantity per package (bundle): 20 pcs or 25 pcs.
Bulk packaging:	5000 pcs on a pallet-box (2,10 x 1,20 x 1,30m)
System code:	GX/IL-L



Application:

The closure strip provides an important finishing of the foundation membrane (so called dimpled/ stud membrane). It constitutes an excellent form of proofing. Prevents condensate and snow from entering into the foundation wall.

Transportation and storage conditions:

The strips can be transported by any means of transport, if they are tied or packed in factory packaging, in a horizontal position, protected from movement. During transportation and storage they should not be exposed to mechanical damage, direct sunlight and temperatures above 50 ° C.

Storage location: dry, cool, even surface.

Maximum number of layers during storage: 15.

This is a system product to all dimpled membranes GXP PLUS and GXP DREN, it is not covered by any separate harmonized norms.

**GRILTEX POLSKA SP. Z O.O., UL. OBORNICKA 7,
ZŁOTKOWO, 62-002 SUCHY LAS**

TEL.(061) 814 85 17, 655 37 51, 0 22 212 84 86, 0600 078 283 FAX. (061) 655 37 50

www.griltex.pl , biuro@griltex.pl, ISO 9001 nr PL004194/P Bureau Veritas Certification

NIP: 777-21-94-858; REGON: 631058608; Sąd Rejonowy Poznań , VIII Wydział Gospodarczy Krajowego Rejestru Sądowego KRS: 0000124014; kapitał zakładowy: 772 000 zł